

Safety Data Sheet (SDS)

Weyerhaeuser Diamond™ Premium Floor Panels

1. Identification

TRADE NAME(S):	Weyerhaeuser Diamond™ Premium Floor Panels
SYNONYMS and/or GRADES:	Weyerhaeuser Diamond™ OSB
PRODUCT USES:	Building Materials
CHEMICAL NAME/CLASS:	Wood Products
MANUFACTURER'S NAME:	Weyerhaeuser
ADDRESS:	220 Occidental Ave S., Seattle, WA 98104
EMERGENCY PHONE (DOT):	(844) 523-4081 (3E Company)
BUSINESS PHONE:	(206) 539-3910

2. Hazard(s) Identification (cont'd.)

<p>Skin Irritation Category 2 (H315)</p> <p>Specific Target Organ Toxicity- Single Exposure (STOT) Category 3 (H335)</p>	<p>Causes skin irritation</p> <p>May cause respiratory irritation</p>	
<p>Eye Irritation Category 2B (H320)</p>	<p>Causes eye irritation</p>	<p>None</p>
<p>Combustible Dust (OSHA Defined Hazard)</p>	<p>If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air</p>	<p>None</p>

*Hazard codes (GHS)

HMIS Rating (Scale 0-4): **Health = 2*** **Fire = 1** **Physical Hazard = 0**
NFPA Rating (Scale 0-4): **Health = 1** **Fire = 1** **Reactivity = 0**

Precautionary Statement(s):

Prevention Statements:

- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from sparks, flame or other heat sources.
- P243: Take precautionary measures against static discharge.
- P261+284: Avoid breathing dust. In case of inadequate ventilation wear an approved respirator suitable for conditions of use.
- P271: Use outdoors or in a well-ventilated area.
- P280: Wear appropriate protective equipment for eye and skin exposure.

Response Statements:

- P304+P340+P313: If inhaled and breathing becomes difficult, remove person to fresh air and keep comfortable for breathing. If symptoms persist, call a doctor or other qualified medical professional.
- P333+P313: If skin irritation or rash occurs get medical advice/attention.
- P352+P264: If on skin wash with plenty of soap and water.
- P362+P364: Take off contaminated clothing and wash before reuse.
- P305+P351+P338: If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do so.

Disposal:

- P501: Dispose of contents in accordance with federal, state and local regulations.

Ingredients of Unknown Acute Toxicity (>1%): NAP

3. Composition/Information on Ingredients

Ingredient(s)	CAS#	
---------------	------	--

6. Accidental Release Measures

Steps to be taken in case Material Is Released or Spilled: Sweep or vacuum up for recovery and disposal. Avoid creating dusty conditions whenever feasible. Maintain good housekeeping to avoid accumulation of wood and resin dust on exposed surfaces. Use approved filtering facepiece respirator (“dust mask”) or higher levels of respiratory protection as indicated and goggles where ventilation is not possible and exposure limits may be exceeded or for additional worker comfort.

7. Handling and Storage

Precautions to be taken in Handling and Storage: Product dust may pose a combustible dust hazard.

Keep away from ignition sources. Avoid eye contact. Avoid prolonged or repeated contact with skin.

Avoid prolonged or repeated breathing of wood dust. Store in well-ventilated, cool, dry place away

from open flame. Sto42uT d(t)-6 (o42uT)(613.2 470.88.962.6 re f* BT 0 scn /TT1 1 Tf -0.002 Tc 0.002 Tw 11.04

10.

16. Other Information

Definition of Common Terms:

ACGIH® = American Conference of Governmental Industrial Hygienists

C = Ceiling Limit

CAS# = Chemical Abstracts System Number

DOT = U. S. Department of Transportation

DSL = Domestic Substance List

[REDACTED] = Identifying Number Assigned to Chemicals Contained in the European Inventory of Existing Chemical Substances (EINECd 23.04 re W n B3.1 (S)2.4 (u)-12.5 7 (i)3.2 tment

Weyerhaeuser Diamond™

Premium Floor Panels

Danger

Wood dust may cause nasopharyngeal cancer and/or cancer of the nasal cavities and paranasal sinuses by inhalation. May cause respiratory, skin and eye irritation.

May form combustible dust concentrations in air if small particles are formed during processing or handling.

Precautions: Do not handle until all safety precautions have been read and understood. Use outdoors or in a wellventilated area. Avoid breathing dust and wear appropriate protective equipment for respiratory, skin or eye exposures. Prevent dust release and accumulations to minimize hazard. Take off contaminated clothing and wash before reuse. Keep dust away from ignition sources such as heat, sparks, and flame

First Aid:

If in eyes rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Contact a qualified medical professional if symptoms persist.

If on skin, wash with soap and water. If skin irritation or rash occurs, get medical advice/attention.